



# WOUND-OUT<sup>®</sup> 480SL

HERBICIDE



Guarantee: **Glyphosate I.P.A 480g/l**  
Classification: **Glycine derivative**  
Formulation: **Soluble Liquid**

### General Description

WOUND-OUT 480SL is a broad spectrum, non-selective systemic herbicide. It works by inhibiting the enzyme EPSPS, thus preventing synthesis of essential aromatic amino acids needed for protein biosynthesis.

WOUND-OUT is formulated with a **Bio-Activator**, thus:

- \* It is quickly absorbed by the weed foliage.
- \* Rapid translocation to roots, stolons, tubers and rhizomes.

WOUND-OUT is used for the control of a wide variety of weeds including annual, biennial and perennial grasses, sedges and broad-leaved weeds. It is used in plantation crops and non-crop land. It is also ideal for clearing vegetation for minimum/zero tillage systems.

### Recommended Application Rates

Crop	Weeds	Rates
Vegetables (Minimum tillage)	Annual Weeds	2l/ha 400ml/20L water
	Perennial Weeds	3l/ha 600ml/20L water
Maize (Zero-tillage)	Annual & perennial grasses; Broad-leaved weeds.	3l/ha 600ml/20L water
Tea, Sugar cane	Annual Weeds, Perennial Weeds.	2l/ha 400ml/20L water
		3l/ha 600ml/20L water
Sugar cane	Annual & perennial grasses; Broad-leaved weeds.	2l/ha Wound-Out + 2kg/ha Tata MOTO (Metribuzin)
Reduced tillage systems.	Kikuyu grass	2l/ha 400ml/20L water

**Caution:** Avoid spraying in windy weather as drift onto desirable vegetation or green plant parts may result in severe destruction.

### Other Suggested Uses

Crop	Timinig	Rates
Coffee	Annual Weeds	2L/ha (400ml/20L water)
	Perennial Weeds	
Non-crop areas/ Construction sites, etc.	Perennial Weeds	3L/ha (600ml/20L water)

### Compatibility:

WOUND-OUT may be tank-mixed with other herbicides such as Tata MOTO (Metribuzin), for greater spectrum of weed control. Do not add any surfactant/sticker/spreader.

### Environment:

This product is inactivated on contact with soil.



*Comelina sp.*  
(wandering jew)



Black jack (*bidens pilosa*)



Kikuyu grass



Couch grass



Sedge grass

### Osho Chemical Industries Ltd.

Industrial Area Office: Osho Complex, Sasio Rd. off Lunga lunga, Industrial Area

Postal Address: P. O. Box 49916 - GPO 00100 Nbi-Kenya

Pilot Line: (+254) 020 391 2000, (+254) 0711-045 000, (+254) 0733-880 480

Customer Service: (+254) 020 391 2500, (+254) 0711-045 500 Fax: (+254) 020 3912600, (+254) 0711-045 600

E-mail: oshochem@oshochem.com Website: www.oshochem.com

